# KMT1-11 MECHANICS TRUCK (19,500 GVWR & 84" CA)

KNAPHEIDE SINCE 1848

Specifications subject to change without notice

#### **BODY**

# Knapheide 6132DLR-44J

- o 11' crane body with torq-isolator crane support system with torsion box understructure
- o A-40 galvanneal steel compartments and doors with 3/16" tread plate floor and 1/8" tread plate tops and backs that are full-seam continuous welded
- Compartment floors and end panels are 12 gauge steel with 14 gauge double panel, hat section reinforced compartment doors
- o Body is completely immersed in Knapheide's electrodeposition prime paint system for superior corrosion resistance
- o (6) Recessed cargo D-ring tie downs installed in floor with a 6,000 lb. maximum capacity
- o (2) Heavy duty aluminum grab handles located on both sides at the rear of the body
- o LED S/T/T lights, clearance lights, and backup lights located at the rear
- 21" Work surface bumper with through compartments operated by stainless steel Thandles
- Vise plate located on work surface bumper
- o 2" Receiver tube mounted below work surface bumper
- o (2) Grip strut flex steps mounted on the bottom of the work surface bumper on both sides
- o 16" High double panel slam tailgate with center latch and flat space for tailgate graphics
- o Knapliner commercial grade spray-on bed liner applied to cargo floor, sides, compartment tops, bulkhead, and tailgate

#### **CRANE**

#### • Stellar 7621 Crane

- o 38,000 ft.-lbs. with 7,500 lbs. maximum capacity and 21' hydraulic reach
- o Planetary winch at 60'/minute speed with 3/8" cable and double-acting cylinders with integral holding valves and filters
- Crane hook, snatch block, boom support, RF wireless remote, and control panel included
- o Crane includes PTO, hydraulic pump for crane, and hydraulic reservoir

## AIR COMPRESSOR

# • Boss 36 CFM Compressor

- Hydraulic compressor with Reelcraft 50' x ½" hose reel and roller fairlead through the street side rear compartment
- o FLR system and underbody air tank included with compressor

#### **COMPARTMENTS**

- 44" High compartments with 60" high street side front vertical compartment with stainless steel 3 point T-handles
  - Street side front vertical compartment has a 7 drawer unit with 3-3" high drawers, 3-5" high drawers, and 1-7" high drawer
  - o Curb side front vertical compartment has (2) gas bottle retainers with both the top and bottom panels vented for air circulation
  - Street side 2<sup>nd</sup> vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
  - Curb side 2<sup>nd</sup> vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
  - o Street side horizontal compartment has parts storage containers
  - o Curb side horizontal compartment has bolt-in divider shelf with (8) dividers
  - O Street side rear vertical compartment has (2) adjustable, 250 lb. maximum load capacity divider shelves with (4) dividers each
  - o Curb side rear vertical compartment has (1) fixed shelf

### **SECURITY**

- Master Locking System
  - o Secures one entire side of compartments with one easy motion and a padlock

### **CAB PROTECTOR**

• Bolt on cab protector with fully punched window

# **AUXILIARY LIGHTING**

• (4) Halogen work lights installed

#### **OUTRIGGERS**

- (2) Outriggers installed
  - o (2) Hydraulic out and hydraulic down located at the rear

### **BACKUP ALARM**

- 97db audible backup alarm
  - o Audible alarm engages when vehicle is put into reverse